

SOLACE

ZERO CLEARANCE DIRECT VENT GAS FIREPLACE



SOLACE SPECIFICATIONS

SOLACE


Flue Top Top Top Top Fuel Natural Gas Propane Natural Gas Propane Input Max. 30,500 BTU 29,000 BTU 40,000 BTU 36,000 BTU Input Min. 29,000 BTU 22,200 BTU 27,000 BTU 30,000 BTU FE (P.4.1-15) 61.98% / 63.92% 67.63% / 69.25% 60.39% / 61.88% 53.79% / 54.90% Log Set LOGF36 LOGF36 LOGF36 LOGF36	Model	MQHBZDV3636N/NE MQHBZDV4236N/NE	MQHBZDV3636LP/LPE MQHBZDV4236LP/LPE	HBZDV4736N HBZDV4736NE	HBZDV4736LP HBZDV4736LPE
Fuel Natural Gas Propane Natural Gas Propane Input Max. 30,500 BTU 29,000 BTU 40,000 BTU 36,000 BTU Input Min. 29,000 BTU 22,200 BTU 27,000 BTU 30,000 BTU FE (P.4.1-15) 61.98% / 63.92% 67.63% / 69.25% 60.39% / 61.88% 53.79% / 54.90%		MIQHBZDV4Z36N/NE	MQHBZDV4Z36LP/LPE	HBZDV4/30NE	HBZDV4/36LPE
Input Max. 30,500 BTU 29,000 BTU 40,000 BTU 36,000 BTU Input Min. 29,000 BTU 22,200 BTU 27,000 BTU 30,000 BTU FE (P.4.1-15) 61.98% / 63.92% 67.63% / 69.25% 60.39% / 61.88% 53.79% / 54.90%	Flue	Тор	Тор	Тор	Тор
Input Min. 29,000 BTU 22,200 BTU 27,000 BTU 30,000 BTU FE (P.4.1-15) 61.98% / 63.92% 67.63% / 69.25% 60.39% / 61.88% 53.79% / 54.90%	Fuel	Natural Gas	Propane	Natural Gas	Propane
FE (P.4.1-15) 61.98% / 63.92% 67.63% / 69.25% 60.39% / 61.88% 53.79% / 54.90%	Input Max.	30,500 BTU	29,000 BTU	40,000 BTU	36,000 BTU
	Input Min.	-,	22,200 BTU	27,000 BTU	,
Log Set LOGF36 LOGF36 LOGF36	FE (P.4.1-15)	61.98% / 63.92%	67.63% / 69.25%	60.39% / 61.88%	53.79% / 54.90%
	Log Set	LOGF36	LOGF36	LOGF36	LOGF36

SOLACE

Model Flue

Model	HBZDV3624N/NE	HBZDV3624LP/LPE	HBZDV4224N/NE	HBZDV4224LP/LPE
Flue	Тор	Тор	Тор	Тор
Fuel	Natural Gas	Propane	Natural Gas	Propane
Input Max.	24,00 BTU	22,000 BTU	24,000 BTU	22,000 BTU
Input Min.	14,000 BTU	15,000 BTU	14,000 BTU	15,000 BTU
FE (P.4.1-15)	50.48% / 52.30%	52.59% / 54.24%	55.69% / 57.81%	57.03% / 59.09%
Log Sets	MQLOGC45	MQLOGC45	MQLOGC45	MQLOGC45
	LOGC42/43/44	LOGC42/43/44	LOGC42/43/44	LOGC42/43/44

TOP FLUE	Height		Front Width		Depth	
MODEL	Actual	Framing	Actual	Framing	Actual	Framing
LOUVERS						
HBZDV36	34 13/16"	35"	36"	36 %"	16 7/16"	17"
HBZDV42	37"	37 3/8"	41 1/8"	42 3/8"	16 7/16"	17"
HBZDV47	43 1/16"	43 1/8"	47 1/16"	47 3/8"	19 7/16"	19 ½"
CLEAN VIEW CIRCULATING KIT						
HBZDV36	34 11/16"	41"	38 1/16"	38 7/16"	18 %"	19 1/2"
HBZDV42	36 ¹³ / ₁₆ "	43"	42 1/16"	42 1/16"	18 ¹⁵ / ₁₆ "	19 ½"
HBZDV47	49"	49 1/8"	48 1/16"	48 %"	21 15/16"	22"



TOP FLUE MODEL VIEWING AREA					
	Width	Height			
HBZDV36	29 ¾"	18 5/8"			
HBZDV42	33 3/8"	20 3/8"			

HBZDV47 39 1/2"

CORNER FRAMING DIMENSIONS (INCHES): LOUVERED UNITS

HBZDV36 HBZDV42 HBZDV47 A 54 13/16" A 58 13/16" A 65 1/4" **B** 36 3/8" **B** 42 3/8" **B** 47 3/8" C 36" C 41 1/8" C 47 1/16" **D** 9 3/16" **D** 8 1/4" **D** 8 15/16" **E** 41 5/8" E 38 3/4" **E** 46 1/8" F 12 3/8" F 13 3/4" F 13 15/16" G 17 %16" **G** 19 ½" **G** 19 11/16" H 27 3/8" H 29 7/16" H 32 5/8"

CORNER FRAMING DIMENSIONS (INCHES): CLEAN VIEW CIRCULATING KIT (CVK)

HBZDV36		HE	HBZDV42		HBZDV47	
Α	59 %"	Α	63 13/16"	Α	70 3/16"	
В	38 1/16"	В	42 1/16"	В	48 %"	
С	38 1/6"	С	42 1/16"	С	48 1/16"	
D	10 11/16"	D	10 11/16"	D	10 %"	
Ε	42 5/16"	Ε	45 1/8"	Ε	49 5/8"	
F	12 3/8"	F	13 ¾"	F	13 ¹⁵ /16"	
G	17 %16"	G	19 1/2"	G	19 11/16"	
Н	29 5/16"	н	31 %"	н	35 1/16"	





Unit Illustrated:

Solace II HBZDV3624N Direct Vent Fireplace MQLOGC45 Oak Log Set, HB36CVCK Designer Clean View Circulating Kit, HB36RLH Herringbone Brick Liner.

SOLACE

Imagine lively gatherings or times of quiet reflection in front of the beautiful Solace II. Available in two sizes, the Solace II allows you to transform your fireplace into something truly unique.

With so much style and attention to detail, the Solace II is available in a range of sizes and styles. You can choose from our mid-efficient rated fireplace for ambiance and taking the chill out of the room, or our higher-efficient version for additional warmth.

Visit www.marquisfireplaces.net to see the latest evolution in fireplaces.

STANDARD FFATURES

- Millivolt or IPI valve system allows operation during a power failure with Hi/Low heat and flame adjustment
- · Dual burner with Realistic Flame Pattern
- · Safety Screen Barrier

OPTIONAL FFATURES

Designer Clean View Circulating Kit:

No Louvers Required

Louvers:

Grills available in Black

Fan Kit:

Heat activated with variable speed control

Accessories:

Log sets or rock sets required

Liners:

Porcelain Reflective Liner or Brick Liners

SOLACE ACCESSORIES







LOG SETS



LOGF36 Fibre Split Oak (SOLACE)

MQLOGC45 Burnt Oak (SOLACE II)

LOGC42 (SOLACE II)





LOGC44 (SOLACE II)

ROCK SETS REQUIRES SUPPORT PLATFORM (SOLACE I ONLY)



MQROCK2 **Natural Rock Set**

LINERS





Porcelain Reflective



Herringbone Brick





Traditional Brick

MQROCK3 Multi-Colored Rock Set

THERMOSTATS







Marquis Fireplaces maintains a program of continuous testing, refinement and improvements of all its products. Some aspect of units shown here may be changed at any time without notice or obligation.

Certified to: ANSI Z21.88-2017 • CSA 2.33-2017 Vented Gas

Fireplace Heaters, CSA 2.17-2017

Note: Components may have to be ordered separately to create a complete unit. Discuss with your local Marquis Dealer for clarification.

Canada ENER UIDE

Look for the **EnerGuide** Gas Fireplace Energy Efficiency Rating in this brochure

Based on CSA P.4.1-15



FOR CALIFORNIA RESIDENTS ONLY:

WARNING! This product can expose you to chemicals including Carbon Monoxide, that is an externally vented by-product of fuel consumption, which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov.

Crafted entirely in Canada, each Marquis fireplace is built to the highest standards and made to last.

LIMITED LIFETIME WARRANTY



2340 Logan Avenue Winnipeg, Manitoba, CAN R2R 2V3 Phone: 204.632.1962 Fax: 204.632.1960 marquisfireplaces.net

Printed in Canada B057 - 03/2020