Professional *Classic*™ Powered Damper gas water heaters

Performance

- FHR: 72 84 gallons
- Recovery rate is up to 40.4 gallons at a 90 degree rise

Self-Diagnostic System

 Electronic gas control for improved monitoring and service



Low Emissions

- Eco-friendly burner, low NOx design
- Meets 40 ng/J NOx requirements

Technology

 24 VAC flue damper, 110 VAC outlet required



- Includes 9-foot cord, 3-prong plug
- Standard Cat. I, double-wall, B-vent,
 3" (4" adaptor included)

What is a Powered Damper?

The 24-volt powered flue damper is positioned atop the unit. It opens and closes automatically in response to gas-burner activity. When the combustion stops, it signals the damper to close, trapping the heat inside the flue and delivering more heat to the water.

Guardian System[™] & Sensor

- Exclusive air/fuel shut-off device
- Maintenance free no filter to clean
- Disables the heater in the presence of flammable vapor accumulation





Combustion Shut-off System

000

Maintenance Free

EcoNet

EcoNet™ enabled WiFi-connected¹ technology and free mobile app gives users control over water systems, allowing for customizable temperature, vacation settings, energy savings and system monitoring at home or away. Visit Rheem.com/EcoNetConnect

- Water sensor detects water outside of the unit and sends an alert via the free EcoNet[™] mobile app to the homeowner
- EcoNet[™] WiFi Kit part number EEWRA631GWH sold separately

† WiFi broadband internet connection required.

Longer Life

 Premium grade anode rod provides long-lasting tank protection

High Altitude Compliant

 Certified to 10,100 ft. above sea level (50-gallon 50K Btu/h model certified to 5,999 feet above sea level)

Plus...

- Dual certified for both potable water and space heating
- Enhanced flow brass drain valve
- Temperature and pressure relief valve included
- Low lead compliant
- Standard replacement parts

Warranty

- 6-Year limited tank and parts warranty*
- With ProtectionPlus™ the 6-year limited tank warranty becomes 10-year ProtectionPlus™ – order part number SP20904 (6 pack only)
- With ProtectionPlus[™] the 6-year limited tank warranty becomes 8-year ProtectionPlus[™] – order part number SP20081 (6 pack only)

*See Residential Warranty Certificate for complete information



Professional *Classic*Powered Damper

38, 40 and 50-Gallon Capacities Up to 40,000 Btu/h Natural and LP Gas




See dimensions chart on back.



Professional Classic™ Power Dampered Specifications

DESCRIPTION					FEATURES					ROUGHING IN DIMENSIONS (SHOWN IN INCHES)									ENERGY INFO.	
T Y P E	NOMINAL GAL. CAP.	RATED GAL. CAP.	MODEL NUMBER	GAS INPUT IN THOUS. BTU/H		RECOVERY IN G.P.H. 90° RISE		FIRST HOUR DEL. G.P.H.		TANK HT.	DIAM.	HT. TO GAS CONN.	VENT SIZE	WATER CONN. CNTR.	HT. TO SIDE T&P VALVE	WATER CONN. SIZE	SHIP. WT.	ENERGY FACTOR	UNIFORM ENERGY FACTOR	
				NAT.	LP	NAT.	LP	NAT.	A	В	С	D	E	F	G	Н	(LBS)	(EF)	(UEF)	
Short	40	39	PROG40S-40N CN67 PD	40	36	40.4	36.4	69	55-1/2	50-1/2	21-3/4	14	3 or 4	8	44	3/4	140	0.67	0.65	
Short	50	48	PROG50S-40N CN67 PD	40	36	40.4	36.4	78	55-1/2	50-1/2	23-3/4	14	3 or 4	8	44	3/4	160	0.67	0.69	
Tall	38	37	PROG40T-40N CN69 PD	40	36	40.4	36.4	85	62-3/4	57-3/4	19-3/4	14	3 or 4	8	52-1/4	3/4	140	0.69	0.70	
Tall	50	48	PROG50T-40N CN67 PD	40	36	40.4	36.4	79	63	58	21-3/4	14	3 or 4	8	52-1/2	3/4	160	0.67	0.69	

Specify LP when ordering. Add gas input and "P' to the model number. Example: PROG40S-36P CN67 PD



In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.