## **4237 Ember-Glo™ Deluxe** PREMIUM TRADITIONAL GAS FIREPLACE





The grandest of our premium fireplaces, the 4237 Ember-Glo<sup>™</sup> Deluxe is a massive showstopper that is perfect for great rooms with its 42" wide by 37" high glass and generous heat output. The magic of the 4237 Ember-Glo<sup>™</sup> Deluxe lies within its ability to express the appeal of an open masonry fireplace while embodying the performance and functionality of today's superior gas heating technology. This top vent fireplace is available as a "Clean Face" model, or you can add the hand-hammered IronWorks<sup>™</sup> Double Doors.

The 4237 Ember-Glo<sup>™</sup> Deluxe is a full feature Deluxe fireplace. Just as the name "Deluxe" implies, this fireplace includes the GreenSmart® Remote Control, 260 CFM Convection Fan, and overhead and Ember-Glo<sup>™</sup> Accent Lights. Add the CoolSmart<sup>™</sup> Wall Kit and install a TV above your fireplace.

# 4237 Ember-Glo<sup>™</sup> Deluxe PREMIUM TRADITIONAL GAS FIREPLACE

## **FIREPLACE XTRORDINAIR** FIREPLACEX.COM

Features & Options You're Gonna Love	
Comfort Control™	YES
Burner Type	Ember-Fyre <sup>®</sup> II
Convection Fan	260 CFM
Accent Lights	OVERHEAD
Ember-Glo™	YES
Cool Smart TV Wall™ Option	YES
Power Exhaust Vent Option	YES
Power Heat Duct Option	TWO
Specifications	
Height (including standoffs)	53-3/4"
Width	59-1/4"
Depth	29-1/4"
Flue Diameter May be reduced. Ask your dealer.	8"
Direct Vent Top Vent	YES
Direct Vent Rear Vent	N/A
Weight	555 lbs.
Glass Viewing Area	1,388 sq. in.
Combustible Min. Mantel Clearances (Measured from base of fireplace to mantle)	55"-57"
Hearth Requirement	None

#### **Optional Decorative Firebacks** Personalize the inside of your fireplace with

one of our many stunning firebacks.



Herringbone Brick

Handmade Brick



Stacked Tan Brick

Black Glass







Classic Oak 9-piece high definition



Mountain Birch 9-piece high definition



Bon-Fyre<sup>™</sup> 10-piece high definition


Performance	
Heating Capacity (Up To)	3,000 Sq. Ft.
BTU Input High to Low (NG)	60,000 - 14,500
BTU Input High to Low (LP)	60,000 - 13,600
Turndown Ratio	76% NG 77% LP
Canadian EnerGuide P4 Efficiency	66.99% NG 68.78% LP
Steady State Efficiency High (Up to)	78.15% NG 80.64% LP
AFUE (Annual Fuel Utilization Efficiency)	62.20% NG 62.80% LP

NOTE: Improper installation of your gas appliance or failure to operate it in accordance to the guidelines detailed in the Owner's Manual may negate your warranty and endanger your home and family. Installation information is available on our website at www.fireplacex.com.

The dimensions and clearances on this page are for reference only!

Refer to the Owner's Manual prior to installation. We recommend all Fireplace Xtrordinair<sup>®</sup> appliances be installed, and maintained on an annual basis by your Specialty Hearth Retailer.

### Choose your Trim Kit or Double Doors



Timberline™ Trim Kit



IronWorks<sup>™</sup> Double Doors

### **Choose Your Log Set**