

# ProBuilder™ 24 Clean Face Collection

## TRADITIONAL GAS FIREPLACE



The ProBuilder 24 Clean Face Deluxe is shown with the Black Glass Fireback, High Definition 10 Piece Birch Log Set, and Lower Trim.

As the smallest model in our lineup, the ProBuilder 24 Clean Face portrait-style fireplace is an excellent choice for intimate spaces in the home, such as bedrooms, bathrooms, and kitchens. The unique vertical profile and “clean face” look of this top vent model complements all décor, while its zonal heating capabilities add comforting warmth to rooms not normally considered for fireplaces.

- Heating Capacity\*: Up to 750 Sq. Ft.
- BTU/Hr Input: MV: 9,500 to 18,000 NG/LP (47% turndown)  
GSB: 9,500 to 18,000 NG/LP (47% turndown)  
Deluxe: 9,500 to 18,000 NG/LP (47% turndown)
- P4 Efficiency: MV: 68.80% NG, 70.14% LP  
GSB/Deluxe: 70.10% NG, 71.57% LP
- Steady State Efficiency: MV: Up to 76.5% NG, 77.52% LP  
GSB/Deluxe: Up to 76.5% NG, 77.64% LP
- Weight: 145 lbs. (66 kg).
- Viewing Area: Tempered Glass: 18" W x 26" H (467 sq. in.)

\*Heating capacity will vary with floor plan, insulation, and outside temperature

### AVAILABLE TWO VERSIONS:

- GSB Model  
GreenSmart® Basic, Electric Ignition, Basic Remote
- Deluxe Model includes enhanced performance features and aesthetic choices, such as the GreenSmart® Remote Control, Ember-Glo™, and a 180 CFM convection fan.

# ProBuilder™ 24 Clean Face Collection

## TRADITIONAL GAS FIREPLACE



### Standard Features GSB Models

Features an economical electronic ignition system.

- Continuous Pilot or Basic GreenSmart® Ignition Modes
- 110 V Power Required, Built-in Automatic Battery Backup
- ON/OFF Wall Switch
- 8 Piece Basic Oak Log Set
- Easy Access Controls

### Optional Accessories for GSB Models

#### Basic GreenSmart® Wireless Thermostat Remote Control

- Manual Setting - ON/OFF controls.
- Thermostat Setting - Fireplace turns ON/OFF to maintain your desired home/room temperature.

#### Convection Fan

Variable speed 180 CFM\* fan helps increase the natural convection of heated air into the room as it circulates around the firebox and glass frame. The fan speed is manually controlled by a rheostat dial. \*Cubic Feet Per Minute

#### Wired Wall Timer

The wired wall timer allows you to set the shut off time of your fireplace in 30 minute increments with a two hour maximum time limit.

#### Ember-Glo™


Ember-Glo™ combines adjustable halogen under-lighting with colored glass and embers to provide an amazingly realistic ember bed effect. ON/OFF and brightness are controlled manually with a rheostat dial.

### Standard Features Deluxe Models

Includes a combination of incredible exclusive features.

- Continuous Pilot or GreenSmart® Ignition Modes
- Choice of Two 10 Piece High Definition Log Sets (Oak or Birch)
- 110 V Power Required, Built-in Automatic Battery Backup
- Ember-Glo™ Halogen Under-lit Accent Lighting
- All Functions Are Controlled From the GreenSmart® Remote
- 180 CFM Variable Speed Convection Fan

### Standard GreenSmart® Multi-Function Wireless Thermostat Remote Control



- Thermostat and Smart Thermostat Modes
- Flame Adjustment (6 Levels)
- Change Between GreenSmart® and Continuous Pilot Modes
- Fan Operation
- Ember-Glo™ ON/OFF
- Comfort Control™ ON/OFF

### CoolSmart TV Wall™

Our optional CoolSmart TV Wall™ Kit allows you to safely install a television above your gas fireplace (either recessed or mounted), without requiring a mantel.



Scan For Manual

### Standard Log Set for GSB Models



### Optional Log Sets for ProBuilder Deluxe Models



### Optional Firebacks

Personalize the inside of your fireplace



Common Brick Fireback



High Gloss Black Glass Fireback